

F23 Minilab Chemistry (Fuji™ CN-16Q™)

C-41/ CN-16Q Developer starter (NQ1-S)

C-41/CN16Q Developer Starter is used to prepare a working tank solution from all our developer replenishers. The easy-to-follow instructions for adding the proper amounts of starter, water and replenisher can be found on the mix instructions of the replenisher kit.

Catalog Number	Mix Size	Shipping Weight
55DE5101	1 L conc.	1.25 kg
55DE51016	6 x 1 L conc.	7.66 kg

CPAC C-41 STD Developer Replenisher (NQ1)

This three-part liquid concentrate produces consistent, high quality negatives at a replenishment rate that is equal conventional C-41 developer. C-41 Standard Developer Replenisher is designed for C-41 film processes, and reduces operating cost and effluent volume. Works well in both the C-41 and the CN-16Q™ processes.

Catalog Number	Mix Size	Shipping Weight
50DE5105	2 x 5 L	1.69 kg
50DE5102	2 x 10 L	3.15 kg

Specifications :

- Time : 3'15"
- Temperature : 38°C +/- 0.2
- Replenishment rate*: 45 ml/film (135x24exp.)

F23 CN-16Q Bleach III Replenisher (NQ2)

Specifically designed for convenience in the CN-16Q™ Fuji 23™ film process, this bleach comes ready-to-use as a replenisher, and does not require starter to make working solution. F23 Bleach reduces effluent and operating cost by replenishing at half the rate of traditional products. Type III Formula delivers high quality processed film without silver retention problems. This product is also a good choice for "one-shot" processors.

Catalog Number	Mix Size	Shipping Weight
55BL5255	2 x 5 L	12.54 kg

Specifications :

- Time : 1' 00"
- Temperature : 35 - 41°C
- Replenishment rate*: 11 ml/film (135x24exp.)

50% Lower Rep. rate

® Fuji and Fujicolor are the registered trademarks of the Fuji Photo Film Co. Ltd.

(*) Actual replenishment rate will depend on utilization, processing environment and film population

CPAC Africa (Pty) Ltd. T/A RT Chem Corporation
Unit B1, Zandpark, Richards Bay Ave.
Kirkney Ext.6, Pretoria, South Africa.
P.O.Box 48431, Hercules, 0030 South Africa

Phone : +/27 (012) 372 0671 or 3
Fax : +/27 (012)372 0674
e-mail : cpac@cpac.co.za
Internet : <http://www.cpacafrika.com>

F23 CN-16Q Fixer & Replenisher (NQ3)

Exclusively designed for use in the CN-16Q™ Fuji 23™ film processors, F23 Bleach and F23 Fixer cascade into a common bleach-fix working tank solution.

Catalog Number	Mix Size	Shipping Weight
55FX5355	2 x 5 L	6.41 kg

Specifications :

- Time : 3' 15"
- Temperature : 35 - 41°C
- Replenishment rate*: 30 ml/film (135x24exp.)

Super Conditioner (NQS) (FSC)

RT/CPAC's Super Conditioner removes the bleach-fix and the soluble silver salts from the film. The Super Conditioner is a one-part powder, which dissolves easily into water.

Catalog Number	Mix Size	Shipping Weight
70ST7519	25 x 10 L	0,05 kg

Specifications :

- Time : 1'40"
- Temperature : 35 - 41°C
- Replenishment rate*: 30 ml/film (135x24exp.)

ML FF Stabilizer & Replenisher (NQ4)

ML FF Stabilizer offers excellent dye stability, reduces water spotting, and is effective in any wash or washless C-41 film process. This one-part liquid concentrate makes both a working tank and replenisher solution.

Catalog Number	Mix Size	Shipping Weight
55ML5412	12 x 10 L	1.56 kg

Specifications :

- Time : 40"
- Temperature : 35 - 41°C
- Replenishment rate*: 20 - 30 ml/film (135x24exp.)

® Fuji and Fujicolor are the registered trademarks of the Fuji Photo Film Co. Ltd.

(*) Actual replenishment rate will depend on utilization, processing environment and film population